

**Miniature Slit Type Flexible Coupling (Type HST)**  
**Material Aluminium/Steel**

Type	Dim. (MM)		Bore Size (MM)			Screw	Misalignment		Speed (RPM)	Torque N.M.
	OD	L	MIN B1	MIN B2	MAX B1 & B2		ANG.	PARALLEL (MM)		
HST1	32	42	8	3	14	M4	2 °	0.15	4800	2
HST2	40	55	8	10	18	M5	2 °	0.20	3800	5
HST3	50	70	12	14	22	M6	2 °	0.20	3100	10
HST4	63	85	14	18	30	M6	2 °	0.20	2400	18

**Disk Flexible Coupling (High Torque Backlash Free)**  
**Double Disk :**

Type	D (MM)	A (MM)	Bore (MM)		L (MM)	M (MM)	Torque (Nm)	Speed (RPM)	Misalignment		Eccentricity (MM)
			B1 (MM)	B2 (MM)					Parallel Offset	Angular Offset	
Df1	40	28	10	14	46	M4	6	3500	+/-0.5	2 °	0.20
Df2	50	39	12	20	52	M5	12	3000	+/-0.6	2 °	0.20
Df3	63	45	16	25	56	M6	19	2400	+/-0.8	2 °	0.30

**Material : Hub – Aluminium, Din-Stainless steel, Dist-Stainless Steel**

**Features :**

- ❖ Compensation of Axial, Radial & Angular Misalignments
- ❖ Long Service life (All steel material)
- ❖ Taper Bore, hubs, are also available (As per your drawings)
- ❖ Simple and fast assembly

**Custom Sizes are also available as per your requirement**

**-: ORDER INFORMATION :-**

